

FINN DIN KABELTYPE HER:

Draka cable	Impedance	Cable group	50Ω BNC Plug	50Ω BNC Jack	3G BNC Plug	3G BNC Jack	12G Korus BNC Plug	12G Korus BNC Jack	Micro BNC Plug	Micro BNC Jack	1.0/2.3 DIN Plug	1.0/2.3 DIN Jack	Jacket O/D	Dielectric O/D	Center conductor O/D	Similar cables:
RG179 B/U	75Ω	AB	n/a	n/a	10-005-B36-AB	10-054-B36-AB	n/a	n/a	67-005-B66-AB	n/a	52-005-B6-AB	n/a	2.54mm	1.6mm	0.31mm	Belden 179DT
0.41/6.9 AF	75Ω	BH	n/a	n/a	10-005-B36-BH	n/a	10-005-W126-BH	10-054-D126-BH	67-005-B66-BH	n/a	52-005-B6-BH	n/a	3.1mm	1.9mm	0.41mm	
0.6/2.8 AF	75Ω	FA	n/a	n/a	10-005-B36-FA	10-054-B36-FA	10-005-W126-FA	10-054-D126-FA	67-005-B66-FA	67-054-B66-FA	52-005-B6-FA	52-054-D6-FA	4.5mm	2.8mm	0.6mm	Belden 1855ENH, Image 360, Percon VK5
HD PRO 0.6/2.8AF	75Ω	FA	n/a	n/a	10-005-B36-FA	10-054-B36-FA	10-005-W126-FA	10-054-D126-FA	67-005-B66-FA	67-054-B66-FA	52-005-B6-FA	52-054-D6-FA	4.5mm	2.8mm	0.6mm	Belden 1855ENH, Image 360, Percon VK5
Ultra HD Pro 50	75Ω	FA	n/a	n/a	10-005-B36-FA	10-054-B36-FA	10-005-W126-FA	10-054-D126-FA	67-005-B66-FA	67-054-B66-FA	52-005-B6-FA	52-054-D6-FA	4.5mm	2.9mm	0.7mm	Belden 1855ENH, Image 360, Percon VK5
RG59	75Ω	AI	n/a	n/a	10-005-B36-AI	10-054-B36-AI	n/a	n/a	n/a	n/a	n/a	n/a	6.15mm	3.7mm	0.59mm	Canford LV-615, URM 70
0.8/3.7 AF	75Ω	FB	n/a	n/a	10-005-B36-FB	n/a	10-005-W126-FB	10-054-D126-FB	67-005-B66-FB	67-054-B66-FB	52-005-B6-FB	52-054-D6-FB	5.9mm	3.7mm	0.8mm	Belden 1505A, Image 720, Percon VK6
0.8L/3.7 Dz	75Ω	FB	n/a	n/a	10-005-B36-FB	n/a	10-005-W126-FB	10-054-D126-FB	67-005-B66-FB	67-054-B66-FB	52-005-B6-FB	52-054-D6-FB	5.9mm	3.7mm	0.8mm	Belden 1505A, Image 720, Percon VK6
1.0/4.8 AF	75Ω	FC	n/a	n/a	10-005-B36-FC	n/a	10-005-W126-FC	10-054-D126-FC	67-005-B66-FC	n/a	52-005-B6-FC	n/a	7.0mm	4.8mm	1.0mm	Belden 1694F, Image 1000, Percon VK7
1.0L/4.8Dz HD PRO FLEX	75Ω	FC	n/a	n/a	10-005-B36-FC	n/a	10-005-W126-FC	10-054-D126-FC	67-005-B66-FC	n/a	52-005-B6-FC	n/a	7.0mm	4.8mm	1.0mm	Belden 1694F, Image 1000, Percon VK7
1.2L/4.8Dz	75Ω	FF	n/a	n/a	10-005-B36-FF	n/a	10-005-W126-FF	10-054-D126-FF	n/a	n/a	n/a	n/a	7.2mm	4.8mm	1.2mm	Sommer 600-0214
Ultra HD Pro 100	75Ω	FF	n/a	n/a	10-005-B36-FF	n/a	10-005-W126-FF	10-054-D126-FF	n/a	n/a	n/a	n/a	7.0mm	4.9mm	1.2mm	Sommer 600-0214
1.4/6.6 AF	75Ω	FH	n/a	n/a	10-005-B36-FH	n/a	n/a	n/a	n/a	n/a	n/a	n/a	9.2mm	6.4mm	1.4mm	Conduclif 14510
1.6/7.3 AF	75Ω	FD	n/a	n/a	10-005-B36-FD	n/a	10-005-W126-FD	10-054-D126-FD	n/a	n/a	n/a	n/a	10.3mm	7.3mm	1.6mm	Belden 9292, Image 2000
RG58	50Ω	AH	10-005-A3-AH	10-054-A3-AH	n/a	n/a	n/a	n/a	67-005-B3-AH (50Ω)	n/a	52-005-B0-AH (50Ω)	n/a	4.95mm	2.95mm	0.91mm	Belden 9203, URM 43
RG213	50Ω	AN	10-005-B3-AN	10-054-A3-AN	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	10.3mm	7.25mm	2.25mm	URM67

FINN KORREKT KRYMPETANG FOR KONNEKTOREN HER:

Connector:	Crimp diameters				Tools:	
3G BNC:	Impedance	Cable group:	Center conductor:	Crimp sleeve:	Professional	Economy
10-005-B36-AB	75Ω	AB	1.07mm	3.25mm		96-336J
10-005-B36-BH	75Ω	BH	1.72mm	4.52mm		96-336J
10-005-B36-FA	75Ω	FA	1.72mm	5.41mm	96-HTS-75A	
10-005-B36-AI	75Ω	AI	1.72mm	6.5mm		96-336-A
10-005-B36-FB	75Ω	FB	1.72mm	6.48mm	96-HTS-76	
10-005-B36-FC	75Ω	FC	1.72mm	8.23mm		96-336-D
10-005-B36-FF	75Ω	FF	1.72mm	8.23mm		96-336-D
10-005-B36-FH	75Ω	FH	2.54mm	10.9mm		96-336-K
10-005-B36-FD	75Ω	FD	2.54mm	10.9mm		96-336-K
<b>3G BNC Jack:</b>						
10-054-B36-AB	75Ω	AB	1.07mm	3.25mm		96-336J
10-054-B36-FA	75Ω	FA	1.72mm	5.41mm	96-HTS-75A	
10-054-B36-AI	75Ω	AI	1.72mm	6.5mm		96-336-A
<b>12G Korus BNC Plug:</b>						
10-005-W126-BH	75Ω	BH	0.95mm	5.41mm	96-HTS-75A	
10-005-W126-FA	75Ω	FA	0.95mm	5.41mm	96-HTS-75A	
10-005-W126-FB	75Ω	FB	1.72mm	6.48mm	96-HTS-76	96-336-D
10-005-W126-FC	75Ω	FC	1.72mm	8.23mm	96-HTS-75A	96-336-D
10-005-W126-FF	75Ω	FF	1.72mm	8.23mm	96-HTS-75A	96-336-D
10-005-W126-FD	75Ω	FD	2.54mm	10.9mm		96-336-K
<b>12G Korus BNC Jack:</b>						
10-054-D126-BH	75Ω	BH	1.07mm	5.41mm	96-HTS-75A	
10-054-D126-FA	75Ω	FA	1.07mm	5.41mm	96-HTS-75A	
10-054-D126-FB	75Ω	FB	1.72mm	6.48mm	96-HTS-76	96-336-D
10-054-D126-FC	75Ω	FC	1.72mm	8.23mm	96-HTS-75A	96-336-D
10-054-D126-FF	75Ω	FF	1.72mm	8.23mm	96-HTS-75A	96-336-D
10-054-D126-FD	75Ω	FD	2.54mm	10.9mm		96-336-K

SPEKIFIKASJONER PÅ KRYMPETANG:

Tool	Center diameters				Sleeve diameters				Cable group	Note:
	Diam 1	Diam 2	Diam 3	Diam 4	Diam 5	Diam 6	Diam 7			
HT-336A	1.72mm	n/a	n/a	5.41mm	6.50mm	n/a	n/a		FA / FB / AI	
HT-336D	1.73mm	n/a	n/a	5.41mm	6.50mm	8.23mm	n/a		FA / FB / FC	
HT-336G	1.09mm	1.73mm	n/a	2.54mm	3.48mm	5.41mm	6.48mm		FA / FB	
HT-336J	1.07mm	1.73mm	1.98mm	2.36mm	3.25mm	3.84mm	4.52mm		AB / AH	
HT-336K	2.54mm	n/a	n/a	3.25mm	10.90mm	n/a	n/a		AN / FD / FH	
96-HTS-43	0.95mm	n/a	n/a	3.25mm	4.52mm	5.18mm	n/a		AB / BH	
96-HTS-75	0.95mm	1.72mm	n/a	5.41mm	8.23mm	n/a	n/a		FA / FC	
96-HTS-76	0.95mm	1.72mm	n/a	5.41mm	6.48mm	n/a	n/a		FA / FB	
96-HTS-75A	0.95mm	1.07mm	1.73mm	5.41mm	8.23mm	n/a	n/a		FA / FC	
96-HTS-77	1.07mm	n/a	n/a	4.52mm	6.48mm	7.06mm	n/a		FC	MicroBNC/DIN only
Paladin 3703 die set	1.25mm	1.69mm	n/a	5.41mm	6.48mm	7.01mm	n/a		FA / FB	

FINN KORREKT KRYMPETANG FOR KONNEKTOREN HER:

Connector:	Crimp diameters				Tools:	
Micro BNC Plug:	Impedance	Cable group:	Center conductor:	Crimp sleeve:	Professional	Economy
67-005-B66-AB	75Ω	AB	0.95mm	3.25mm	96-HTS-43	
67-005-B66-BH	75Ω	BH	0.95mm	4.52mm	96-HTS-43	
67-005-B66-FA	75Ω	FA	0.95mm	5.41mm	96-HTS-75A	
67-005-B66-FB	75Ω	FB	0.95mm	6.48mm	96-HTS-76	
67-005-B66-FC	75Ω	FC	1.07mm	7.06mm	96-HTS-77	
67-005-B3-AH (50Ω)	50Ω	AH	1.72mm	5.41mm	96-HTS-76	96-336A
<b>Micro BNC Jack:</b>						
67-054-B66-FA	75Ω	FA	0.95mm	5.41mm	96-HTS-75A	
67-054-B66-FB	75Ω	FB	0.95mm	5.41mm	96-HTS-76	
<b>1.0/2.3 DIN Plug:</b>						
52-005-B6-AB	75Ω	AB	0.95mm	3.25mm	96-HTS-43	
52-005-B6-BH	75Ω	BH	0.95mm	4.52mm	96-HTS-43	
52-005-B6-FA	75Ω	FA	0.95mm	5.41mm	96-HTS-75A	
52-005-B6-FB	75Ω	FB	0.95mm	6.48mm	96-HTS-76	
52-005-B6-FC	75Ω	FC	1.07mm	7.06mm	96-HTS-77	
52-005-B0-AH (50Ω)	50Ω	AH	1.72mm	5.41mm	96-HTS-76	96-336A
<b>1.0/2.3 DIN Jack:</b>						
52-054-D6-FA	75Ω	FA	0.95mm	5.41mm	96-HTS-76	
52-054-D6-FB	75Ω	FB	0.95mm	6.48mm	96-HTS-76	
<b>50Ω BNC Plug:</b>						
10-005-A3-AH	50Ω	AH	1.72mm	5.41mm	96-HTS-76	96-336A
10-005-B3-AN	50Ω	AB	2.54mm	10.9mm		96-336K
<b>50Ω BNC Jack:</b>						
10-054-A3-AH	50Ω	AH	1.72mm	5.41mm	96-HTS-76	96-336A
10-054-A3-AN	50Ω	AN	2.54mm	10.9mm		96-336K